Technical datasheet

Leica DA175

A compact transmitter for active tracing with the DD100 series. Direct connection, induction and an optional clamp offer a choice of signal application methods.



Operating time depends on the power level, signal application method and batteries. The 8 and 33 kHz values are mode labels; the nominal frequencies are 8.192 and 32.768 kHz.

Induction frequencies	8 and 33 kHz
Direct connection	8 and 33 kHz; 512 and 640 Hz
Output power	Up to 1 W at 300 Ω
Ingress protection	IP67: cover closed; IP65: cover open
Power supply	4 × D / LR20 alkaline batteries
Operating temperature	From -20°C to +50°C
Dimensions	250 × 206 × 113 mm
Operating time	Up to 30 h of intermittent use at 20°C

Original adaptation and translation: geoscanners.pl. Based on Leica Geosystems materials.

Photos and technical data: Leica Geosystems / Hexagon.

GeoScanners
SKLEP INTERNETOWY

Choose equipment for your work

Leica utility locators: kit selection, demonstrations and purchase advice.

- when it has to be right





Dr Eng Michał Dąbrowski

+48 796 837 252

michal.sklep@geoscanners.pl

Kraków

Eng Tomasz Dąbrowski

+48 505 655 881

tomasz.sklep@geoscanners.pl

Warszawa

Talk to our team

sklep.geoscanners.pl

sklep@geoscanners.pl

Original adaptation and translation: geoscanners.pl. Based on Leica Geosystems materials.

Photos and technical data: Leica Geosystems / Hexagon.