Kit datasheet

# Kit Leica DD130 + DA175 with Digicat clamp

A kit for searching for and actively tracing conductive utilities. The locator receives the signal, while DA175 applies it to a selected line.




### Contents of this GeoScanners offer

- 1 × Leica DD130 locator
- 1 × Leica DA175 transmitter
- Connection leads with crocodile clips
- Carry bag
- Digicat 100 mm transmitter clamp (850280)

## Specifications of the kit instruments

| | |
|---|---|
| **DD130 - Active frequencies** | 8 and 33 kHz; 512 and 640 Hz |
| **DD130 - Line depth*** | 0.3-3 m |
| **DD130 - Sonde depth*** | Up to 9.99 m |
| **DD130 - Ingress protection** | IP54 |
| **DD130 - Power supply** | 6 × AA / LR6 alkaline batteries |
| **DA175 - Output power** | Up to 1 W at 300 Ω |
| **DA175 - Direct connection** | 8 and 33 kHz; 512 and 640 Hz |
| **DA175 - Power supply** | 4 × D / LR20 alkaline batteries |

* Depth readings require a suitable, undistorted signal. A compatible transmitter is required for a line. Sonde range also depends on the sonde model and its surroundings. The instrument does not directly detect a non-conductive plastic pipe.

Original adaptation and translation: geoscanners.pl. Based on Leica Geosystems materials.

Photos and technical data: Leica Geosystems / Hexagon.

GeoScanners
SKLEP INTERNETOWY

# Choose equipment for your work

Leica utility locators: kit selection, demonstrations and purchase advice.

- when it has to be right






**Dr Eng Michał Dąbrowski**

+48 796 837 252

michal.sklep@geoscanners.pl

Kraków

**Eng Tomasz Dąbrowski**

+48 505 655 881

tomasz.sklep@geoscanners.pl

Warszawa


## Talk to our team

**sklep.geoscanners.pl**

sklep@geoscanners.pl

Original adaptation and translation: geoscanners.pl. Based on Leica Geosystems materials.

Photos and technical data: Leica Geosystems / Hexagon.