Kit datasheet

Kit Leica DT100 + DE100 - Li-Ion and chargers

An expanded kit with Li-Ion power. It includes two rechargeable batteries and two chargers, while retaining the battery holders for both instruments.



Contents of this GeoScanners offer

- 1 × Leica DT100 locator
- 1 × Leica DE100 transmitter
- Battery holders: AA for DT100 and D/LR20 for DE100
- Connection leads with crocodile clips
- Earth stake
- Carry bag
- 2 Li-Ion batteries: for DT100 and DE100
- 2 chargers: for DT100 and DE100

Specifications of the kit instruments

DT100 - Frequency range	50 Hz-200 kHz
DT100 - Depth readings*	Up to 6 m automatically; up to 11 m by button
DT100 - Depth accuracy*	Up to 3 m: ±5% active / sonde; ±10% passive
DE100 - Output power	Up to 10 W with Li-Ion; up to 5 W with alkaline batteries
DT100 / DE100 - Ingress protection	IP65
DT100 / DE100 - Operating temperature	From -20°C to +50°C

This kit does not include a clamp.
* Depth reading limits are not guaranteed detection depths. Accuracy applies to a single, undistorted signal under the conditions specified by the manufacturer. Range depends on the signal, ground, utility and sonde.
Above 45 kHz, the maximum power is 1 W. The power available on the utility also depends on the load and connection method.

Original adaptation and translation: geoscanners.pl. Based on Leica Geosystems materials.

Photos and technical data: Leica Geosystems / Hexagon.

GeoScanners
SKLEP INTERNETOWY

Choose equipment for your work

Leica utility locators: kit selection, demonstrations and purchase advice.

- when it has to be right





Dr Eng Michał Dąbrowski

+48 796 837 252

michal.sklep@geoscanners.pl

Kraków

Eng Tomasz Dąbrowski

+48 505 655 881

tomasz.sklep@geoscanners.pl

Warszawa

Talk to our team

sklep.geoscanners.pl

sklep@geoscanners.pl

Original adaptation and translation: geoscanners.pl. Based on Leica Geosystems materials.

Photos and technical data: Leica Geosystems / Hexagon.